LVRCTL8SC

MODELO

Bebedero de dos niveles refrigerado, con filtro

Especificaciones del fabricante · Configuración del modelo



SKU / modelo	LVRCTL8SC
Configuración	Dos bebederos a distinta altura
Filtración	Filtro integrado · capacidad nominal 1,500 galones
Activación	Botón mecánico frontal
Enfriamiento	8 GPH a 50 °F; entrada 80 °F, ambiente 90 °F
Eléctrico	115 V / 60 Hz · 5 A · 575 W
Montaje	Sobre muro · interiores
Acabado	Acero inoxidable
Dimensiones	36-5/16 × 18-5/8 × 27-1/8 pulgadas (L × A × H)
Peso de embarque	Aproximadamente 97 lb
Certificaciones	ADA según instalación · UL 399 · NSF/ANSI 61 y 372

Ver producto y comprar →

Repuestos correspondientes

Cartucho WaterSentry VII 51299C (1,500 galones), identificado en el original del fabricante. Refacción bajo pedido: solicite cotización a ventas@teknespure.mx. No se asigna 51300C como equivalente.

Cotizar refacciones de servicio →

Use agua potable segura. La instalación y el mantenimiento deben seguir el original del fabricante y la normativa local. Las condiciones de certificación se consultan en el documento original.

Documentación del fabricante

Se conserva el original del modelo o familia aplicable. Consulte sus planos y procedimientos completos antes de intervenir el equipo.

Abrir ficha original independiente

Abrir manual del modelo

Soporte: soporte@teknespure.mx · Ventas: ventas@teknespure.mx

ELKAY®
SPECIFICATIONS

Elkay® Wall Mount Vandal Resistant Bi-level ADA Cooler Filtered Refrigerated Stainless
Model LVRCTL8SC

PRODUCT SPECIFICATIONS

Elkay® Wall Mount Vandal Resistant Bi-level ADA Cooler Filtered Refrigerated Stainless. Chilling Capacity of 8.0 GPH (gallons per hour) of 50° F drinking water, based on 80° F inlet water and 90° F ambient, per ASHRAE 18 testing. Features shall include Filtered, Vandal Resistant. Furnished with Vandal Resistant bubbler. Mechanical Front Bubbler Button activation. Product shall be Wall Mount (On Wall), for Indoor applications, serving 2 station(s). Unit shall be certified to UL 399 and CAN/CSA C22.2 No. 120.

Special Features:	Filtered, Vandal Resistant
Finish:	Stainless Steel
Power:	115V/60Hz
Bubbler Style:	Vandal Resistant
Activation by:	Mechanical Front Bubbler Button
Mounting Type:	Wall Mount (On Wall)
Chilling Capacity*:	8.0 GPH
Full Load Amps	5
Rated Watts:	575
Dimensions (L x W x H):	36-5/16" x 18-5/8" x 27-1/8"
Approx. Shipping Weight:	97 lbs.
Installation Location:	Indoor
No. of Stations Served:	2
*Based on 80° F inlet water & 90° F ambient air temp for 50° F chilled drinking water.	

- Mechanically-Activated unit continues to supply water in event of service disruptions.
- Filter is certified to NSF 42 and 53 for lead, cyst, particulate, chlorine, taste and odor reduction. 1,500 gal. capacity.

COOLING SYSTEM

- Compressor: Hermetically-sealed, reciprocating type, single phase. Sealed-in lifetime lubrication.
- Condenser: Fan cooled, copper tube with aluminum fins. Fan motor is permanently lubricated.
- Cooling Unit: Combination tube-tank type. Continuous copper tubing with is fully insulated with EPS foam that meets UL requirements for self-extinguishing material.
- Refrigerant Control: Refrigerant R-134a is controlled by accurately calibrated capillary tube.
- Temperature Control: Easily accessible enclosed adjustable thermostat is factory preset. Requires no adjustment other than for altitude requirements.



Included with Product: **Water Cooler, Filter**

Ships in one box.

A Century of Tradition and Quality.
For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.

PRODUCT COMPLIANCE

ADA & ICC A117.1

ASME A112.19.3/CSA B45.4

CAN/CSA C22.2 No. 120

NSF/ANSI 42, 53, 61 (Q≤1), 372 (lead free), & 401

UL 399

Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.

Installation Instructions (PDF) - 98958C

5 Year Limited Warranty on the refrigeration system of the unit. Electrical components and water system are warranted for 12 months from date of installation. **Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty.**

Warranty (PDF)

PART:_____QTY: _____

PROJECT:_____

CONTACT:_____


DATE:_____

NOTES:_____

APPROVAL:_____

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

teknes
Distribuidor autorizado Elkay en México
Venta, instalación, refacciones y soporte técnico
WhatsApp 56 1066 3198 · ventas@teknespure.mx · Tel. 55 5524 2072 · teknespure.mx
Escanea para soporte, manual y refacciones
LVRCTL8SC

Optional Accessories		
51299C	Elkay WaterSentry® Lead + Microplastics NSF/ANSI Certified Filter (Coolers & Fountains) Spec Sheet (PDF)	
MLP200	In-wall Carrier for Bi-level On-wall Bottle Fillers Coolers & Fountains Spec Sheet (PDF)	
98324C	Cane Apron for HAC HVR EMABF & VRC Models (Stainless) Spec Sheet (PDF)	
98481C	Bubbler Kit Water-Efficient Vandal-Resistant Spec Sheet (PDF)	

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

teknes
Distribuidor autorizado Elkay en México
Venta, instalación, refacciones y soporte técnico
WhatsApp **56 1066 3198** · ventas@teknespure.mx · Tel. 55 5524 2072 · **teknespure.mx**
Escanea para soporte, manual y refacciones
LVRCTL8SC

Elkay® Wall Mount Vandal Resistant Bi-level ADA Cooler Filtered Refrigerated Stainless
Model LVRCTL8SC

Open space rough-in design permits new installation or replacement of existing fountains and coolers with this Elkay cooler when rough-in is within the outline shown.

IMPORTANT! INSTALLER PLEASE NOTE:
This water cooler has been designed and built to provide water to the user which has not been altered by materials in the cooler waterways.


The grounding of electrical equipment such as telephone, computers, etc to water lines is a common procedure. This grounding may be in the building or occur away from the building. This grounding can cause electrical feedback into a water cooler creating an electrolysis which creates a metallic taste or causes an increase in the metal content of the water. This condition is avoidable by installing the cooler using the proper materials as shown below.

NOTICE


The water cooler must be connected to the water supply using a dielectric coupling. The cooler is furnished with a non-metallic strainer which meets this requirement. The drain trap which is provided by the installer should also be plastic to completely isolate the cooler from the building plumbing system.

Simultaneous operation of both bubblers on a bi-level unit may not be possible depending on water supply pressure. If simultaneous operation is desired, please ensure a minimum of 65 psi supply. Lower pressure may be possible for non-filtered and/or non-refrigerated installations.


OPERATION OF QUICK CONNECT FITTINGS



Pushing tube in before pulling it out helps to release tube



WaterSentry® VII Filter System



REDUCE HEIGHT BY 3 INCHES FOR INSTALLATION OF CHILDRENS ADA COOLER

LEGEND
A = Recommended water supply location. Shut off valve (not furnished) to accept 3/8" O.D. unplated copper tube connect. Up to 3" (76mm) maximum out from wall.
B = Recommended waste outlet location. To accomodate 1-1/4" nominal drain. Drain stub 2" (51mm) out form wall.
C = 1-1/2" Trap (not furnished).
D = Electrical Supply (3) Wire Box.
E = Insure proper ventilation by maintaining 6" (152mm) (min.) clearance from cabinet louvers to wall.
F = 7/16" (11mm) Bolt holes for fastening to wall.

NOTE: New installations must use Ground Fault Circuit Interrupter (GFCI).

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

teknes
Distribuidor autorizado Elkay en México
Venta, instalación, refacciones y soporte técnico
WhatsApp 56 1066 3198 · ventas@teknespure.mx · Tel. 55 5524 2072 · teknespure.mx
Escanea para soporte, manual y refacciones
LVRCTL8SC